Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC	
Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria	

Model identifier: 21860	1
-------------------------	---

Type of I	ight sc	ource:
-----------	---------	--------

Lighting techno	logy used:	LED	Non-directional or directional:	NDLS		
Light source cap	o-type	Connector				
(or other electri	ic interface)					
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable	e light source:	No	Envelope:	-		
High luminance	light source:	No				
Anti-glare shield	d:	No	Dimmable:	Yes		
		Product para	meters			
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consur mode (kWh/10 up to the neare	00 h), rounded	4	Energy efficiency class	E		
dicating if it refe a sphere (360º)	s flux (φuse), iners to the flux in, in a wide cone arrow cone (90°)	500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	40006500		
On-mode pow pressed in W	ver (P _{on}), ex-	4,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
(P _{net}) for CLS, (candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90		
Outer dimen-	Height	40	Spectral power dis-	See image		
sions without	Width	121	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	445	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,440		
		nates (x and y)	0,403		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	56	Survival factor	1,00		
the lumen maintenance factor	0,98				

(a)'-': not applicable; (b)'-': not applicable;

