

WEEE Number: 80133970

INSTRUCTION MANUAL

LED PANEL







TECHNICAL DATA

MODEL	VT-61106	VT-61109	VT-61112	VT-61118
SKU	6982	6983	6984	6985
WATTS	6W	9W	12W	18W
DIRECT CONNECT VOLTAGE	DC: 12-18V	DC: 24-48V	DC: 24-28V	DC:36-72V
BEAM ANGLE	120°	120°	120°	120°
CRI	>80	>80	>80	>80
OPERATION TEMPERATURE	-20°C to +40° C			
BODY TYPE	Aluminium	Aluminium	Aluminium	Aluminium
DIMENSION	Ø120 x 12 mm	Ø145 x 18 mm	Ø170 x 12 mm	Ø225 x 12 mm
CUT OUT SIZE	Ø110 mm	Ø133 mm	Ø160 mm	Ø210 mm

INTRODUCTION & WARRANTY

Thank you for selecting and buying V-TAC product. V-TAC will serve you the best. Please read these instructions carefully before starting the installation and keep this manual handy for future reference. If you have any another query, please contact our dealer or local vendor from whom you have purchased the product. They are trained and ready to serve you at the best. The warranty is valid for 2 years from the date of purchase. The warranty does not apply to damage caused by incorrect installation or abnormal wear and tear. The company gives no warranty against damage to any surface due to incorrect removal and installation of the product. The products are suitable for 10-12 Hours Daily operation. Usage of product for 24 Hours a day would void the warranty. This product is warranted for manufacturing defects only.



MULTI-LANGUAGE MANUAL QR CODE

Please scan the QR code to access the manual in multiple languages.

WARNING

- 1. Please make sure to turn off the power before starting the installation.
- 2. Installation must be performed by a qualified electrician.
- 3. The light source of this luminaire is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced.
- 4. For Indoor Use only




This marking indicates that this product should not be disposed of with other household wastes.



Luminaires not suitable for covering with thermally insulating material.











Caution, risk of electric shock.

INSTALLATION DIAGRAM









- 1. Cut a hole as per the cutout size provided.
- 2. Connect the Live and Neutral wires.
- 3. Hold the two clips back against the panel light and push it into the hole. Allow the springs to pull the light up to the ceiling.
- 4. Switch ON the power and test.













