## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC House, Kelpatrick Road, Slough, Berkshire, SL1 6BW, UK

## Model identifier: 2013

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	DC Female				
(or other electric interface)	connector				
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

		Fibuuct parai	ileters			
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consu mode (kWh/10 up to the neare	00 h), rounded	3	Energy efficiency class	E		
indicating if it r in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide in a narrow cone	400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	10 000		
On-mode p expressed in W	oower (P <sub>on</sub> ),	3,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	4	Spectral power	See image		
dimensions without	Width	8	distribution in the	in last page		
	Depth	500	1	Page 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity	0,140		
		coordinates (x and y)	0,050		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	-100	Survival factor	1,00		
the lumen maintenance factor	0,96				
(2)	1	1			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

