

Product Spec Sheet



VT-6236 36W LED PANEL 600x600MM WITH LIFUD DRIVER 4000K



FEATURES

- Powerful LED light source with lumen efficeincy of LM/W
- Strong and sturdy Aluminium + PS + PP body
- Fitted with high efficiency SMD LED Chips
- Compatible driver SKU 6614(Not Included)
- Easy to connect driver for quicker installation
- Suitable for offices, conference rooms, showrooms, lobbies, cabins, kitchens etc.

TECHNICAL INFORMATION

Dimmable:	No	
Output Voltage:	DC:25-42V	
Color Temperature:	4000K	
Model:	VT-6236	
Watts:	36	
Lumens:	3240	
Input Power:	AC:220-240V, 50/60Hz	
Unit Color:	White	
Color for Web:	Day White	
Body Type:	Aluminium + PS + PP	
Dimension:	595x595x8.5mm	
Operation Temperature:	-20°C to +40°C	
Instant Start:	0-100% in <1s	
On/Off Cycles:	>10000	
Output Current:	850mA	
Shape:	Square	
PF:	>0.9	
LED Chip Type:	SMD	
Beam Angle:	120°	
Input Current:	0.18A	
CRI:	>80	
IP Rating:	IP20	
Long Life:	20,000 Hours	
Energy Saving:	80 Energy	
Retail Pack:	1pc	
IK Rating:	IK05	
Driver Brand:	LIFUD	
EMC Certificate:	Check the certificate	
LVD Certificate:	Check the certificate	

IP20 STANDARD

ROHS Certificate:



LISTING DETA	AII C

SKU: 8082 Model: VT-6236 **PACKAGING**

Gross Weight (Kgs): 2.283333
Unit CBM: 0.00907725

MASTER BOX PACKAGING

Check the certificate

 Box Qty:
 6

 Qty Per Pallet:
 150

EAN:	3800157646857	Dimension:	595x595x8.5mm	Length (Box) mm:
Commodity Code:	9405109890			Width (Box) mm:

Length (Box) mm:	610
Width (Box) mm:	20
Height (Box) mm:	600