



VT-272 200W PHOTOCELL SENSOR FLOODLIGHT SAMSUNG CHIP 6500K



FEATURES

- High quality Light Sensor Floodlight with a lumen output of 100LM/W
- Designed with high efficiency LED Samsung Chips
- Light Sensor function with no turning on/off required
- When natural light is above 140Lux floodlight will be auto off and below 140Lux will be auto on
- Light Sensor Floodlight donot detect any motion
- Built Strong and durable with Die Cast Aluminium Corrosion resistant design
- Perfectly built for outdoor with Ingress protection of IP65
- Application Facade lighting, lobby, garage, passage, parking lot and many more

TECHNICAL INFORMATION

Dimmable:	No
Color Temperature:	6500K
Model:	VT-272
Watts:	200
Lumens:	20000
Input Power:	AC:220-240V, 50Hz
Unit Color:	Black
Color for Web:	White
Body Type:	Diecast Aluminium
Dimension:	371x57x458.5mm
Operation Temperature:	-20°C to +45°C
Instant Start:	0-100% in <1s
On/Off Cycles:	>15000
No. Of Led:	320
LED Chip Solution:	9V 100mA
PF:	>0.9
LED Chip Type:	SMD-Samsung Chip
Beam Angle:	100°
CRI:	>80
Downward LOR (%):	100
Upward LOR (%):	0
Energy Rating Label:	E (2021)
IP Rating:	IP65
Long Life:	25,000 Hours
Energy Saving:	85 Energy
Sensor Type:	Light Sensor
IK Rating:	IK05
lumens per watt:	100
Samsung:	Yes





LISTING DETAILS

SKU:	20183
Model:	VT-272
EAN:	3800157660518

PACKAGING

Gross Weight (Kgs):	4.92
Unit CBM:	0.014548
Dimension:	371x57x458.5mm

MASTER BOX PACKAGING

Box Qty:	2
Qty Per Pallet:	92
Lenath (Box) mm:	376

_____ Commodity Code:

......

94054210

_....

.... Width (Box) mm: 62 Height (Box) mm: 463