







LED Innovative Lights

What better way to light up your living spaces, than with a lighting product that uses only solar energy. With absolutely zero wiring required - this product can function for up to 24 hours with just 6-7 hours of sunlight charging. With an inbuilt sensor, the product lights up upon detection of movement - hence there is no wastage of energy by any means.



Product Features

-  ZERO Electricity Cost
-  PIR Detective
-  Outdoor
-  Solar Powered
-  Light on/off automatically
-  Cordless

Applications

Suitable for Outdoor and Indoor Lighting


White

1.5W VT-767

3000K Warm White } 7096
4000K Day White }

BOX QTY.
 20

EAN Code
3800157616966



IP65
RATED

Watts:	1.5W	Sensing Range:	2-6 mtrs
Voltage:	3.7V Lithium Battery 1200mA	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	200lm	Working Time:	Min 8 hrs and Max 24 hrs
Color:	4000K + 3000K	Protection Rating:	IP65
No. of LED:	10pcs (Front 8pcs, Back 2 pcs)	Material:	High quality Mono crystal Silicon
Detecting Angle:	120°	Dimension:	152 x 96 x 83.8mm




Black

1.5W VT-767

3000K Warm White } 7097
4000K Day White }

BOX QTY.
 20

EAN Code
3800157616973




IP65
RATED

Watts:	1.5W	Sensing Range:	2-6 mtrs
Voltage:	3.7V Lithium Battery 1200mA	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	200lm	Working Time:	Min 8 hrs and Max 24 hrs
Color:	4000K + 3000K	Protection Rating:	IP65
No. of LED:	10pcs (Front 8pcs, Back 2 pcs)	Material:	High quality Mono crystal Silicon
Detecting Angle:	120°	Dimension:	152 x 96 x 83.8mm

White
1.5W VT-767-2
 8276 - 4000K Day White

BOX QTY.
20
 EAN Code
 3800157627931




Watts:	1.5W	Sensing Range:	2-6 mtrs
Voltage:	3.7V Lithium Battery 1200mA	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	220lm	Working Time:	Min 5-8 hrs and Max 24 hrs
Color:	4000K	Protection Rating:	IP65
No. of LED:	14pcs (Front 12pcs, Back 2 pcs)	Material:	ABS+PC
Detecting Angle:	120°	Dimension:	144.5 x 96 x 79 mm



Black
1.5W VT-767-2
 8277 - 4000K Day White

BOX QTY.
20
 EAN Code
 3800157627948



Watts:	1.5W	Sensing Range:	2-6 mtrs
Voltage:	3.7V Lithium Battery 1200mA	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	220lm	Working Time:	Min 5-8 hrs and Max 24 hrs
Color:	4000K	Protection Rating:	IP65
No. of LED:	14pcs (Front 12pcs, Back 2 pcs)	Material:	ABS+PC
Detecting Angle:	120°	Dimension:	144.5 x 96 x 79 mm

White & Grey

2W VT-718


- 9853 - 3000K Warm White
- 9854 - 4000K Day White
- 9852 - 6000K White

BOX QTY.

12

EAN Code

- 3800157622806
- 3800157622813
- 3800157622790



Watts:	2W	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	200lm	Working Time:	Min 5-8 hrs and Max 24 hrs
Color:	3000K , 4000K , 6000K	Protection Rating:	IP65
No. of LED:	18pcs (SMD 2835)	Material:	ABS + PC
Voltage:	3.7V Lithium Battery 1200 mAh	Size:	152 x 158.5x 123.5mm
Detecting Angle:	120°	Housing color:	White + Grey
Sensing Range:	2-6 mtrs		



White & Black

3W VT-768


- 3000K Warm White } 7523
- 4000K Day White }

BOX QTY.

20

EAN Code

3800157619363



Watts:	3W	Sensing Range:	2-6 mtrs
Voltage:	3.7V Lithium Battery 2000mAh	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	400lm	Working Time:	Min 5-8 hrs and Max 24 hrs
Color:	4000K + 3000K	Protection Rating:	IP65
No. of LED:	30pcs (Front 28pcs, Back 2 pcs)	Material:	ABS + PC
Detecting Angle:	60°	Dimension:	140 x 212 x 109.2

White & Black
6.8W VT-767-7


8278 - 4000K Day White

BOX QTY.

20

EAN Code

3800157627955



IP65
 RATED

Watts:	6.8W	Sensing Range::	2-6 mtrs
Voltage:	3.7V Lithium Battery 1200mA	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	800lm	Working Time:	Mode A: 5 hours, Mode B: 2-3 nights
Color:	4000K		Mode C: 3-4 nights
No. of LED:	60pcs (Front 56pcs, Back 4 pcs)	Protection Rating:	IP65
Detecting Angle:	120°	Material:	ABS+PC
		Dimension:	270 x 221 x 109.2 mm



Black
6.8W VT-767-7


8279 - 4000K Day White

BOX QTY.

20

EAN Code

3800157627962



IP65
 RATED

Watts:	6.8W	Sensing Range:	2-6 mtrs
Voltage:	3.7V Lithium Battery 1200mA	Charging Time:	6-7 hrs Sunlight Charging
Lumens:	800lm	Working Time:	Mode A: 5 hours, Mode B: 2-3 nights
Color:	4000K		Mode C: 3-4 nights
No. of LED:	60pcs (Front 56pcs, Back 4 pcs)	Protection Rating:	IP65
Detecting Angle:	120°	Material:	ABS+PC
		Dimension:	270 x 221 x 109.2 mm

Wireless Lights Switch Kit

Introducing the next generation self powered wireless switch, functions using RF receiver making it a hassle free experience. Offering a push button feature and a control distance up to 30 meters.



No Wiring



Wireless



Battery Free



Battery Free Wireless One Gang Switch Set

VT-541

EAN Code

BOX QTY.

8229

3800157624336

50

Switch

Working Type: **Push -Button**

Power Mode: **Self Powered**

Control Distance: **Up to 30 meters**

Switch Lifetime: **>200,000**

Operating Temp: **-5~40°C**

Humidity: **0-95%RH**

Dimensions: **Ø70X15.5mm**

IP Rating: **IP20**

Receiver

Input Voltage: **AC:200-265V,50/60Hz**

Load Power: **Max 200W**

Controller: **RF Receiver**

Dimensions: **D:48x25mm**

Switch Mounting Base

VT-540

EAN Code

BOX QTY.

8231

3800157624336

200

Dimensions: **86 x 86 x 11mm**



No Wiring



Wireless



Battery Free



Battery Free Wireless Two Gang Switch Set

VT-542

EAN Code

BOX QTY.

8230

3800157624343

20

Switch

Working Type:	Push -Button
Power Mode:	Self Powered
Control Distance:	Up to 30 meters
Switch Lifetime:	>200,000
Operating Temp:	-5~40°C
Humidity:	0-95%RH
Dimensions:	Ø70X15.5mm
IP Rating:	IP20

Receiver

Input Voltage:	AC:200-265V,50/60Hz
Load Power:	Max 200W
Controller:	RF Receiver
Dimensions:	D:48x25mm

Switch Mounting Base

VT-540

EAN Code

BOX QTY.

8231

3800157624336

200

Dimensions: **86 x 86 x 11mm**

