## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC  Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria  Model identifier: 212623  Type of light source:									
						Lighting technology used:	LED	Non-directional or directional:	NDLS
						Light source cap-type (or other electric interface)	+ve and -ve		
						Mains or non-mains:	NMLS	Connected light source (CLS):	No
						Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No								
Anti-glare shield:	No	Dimmable:	Only with specific dimmers						
Product parameters									
Parameter	Value	Parameter	Value						
	General product p	parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	8	Energy efficiency class	F						
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	750 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000						
On-mode power (P <sub>on</sub> ), expressed in W	8,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00						
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRIvalues that can be set	80						

4

Spectral

distribution in the

power

Outer

dimensions

Height

Width

See image

in last page

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	1 000	range 250 nm to 800 nm, at full-load		
Claim of equiva	lent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
			Chromaticity	0,378	
			coordinates (x and y)	0,379	
Parameters for LED and OLED light sources:					
R9 colour rende	ring index value	12	Survival factor	1,00	
the lumen main	tenance factor	0,96			

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;

